

**SN5414, SN54LS14,  
SN7414, SN74LS14**  
**HEX SCHMITT-TRIGGER INVERTERS**  
SDLS049B – DECEMBER 1983 – REVISED FEBRUARY 2002


- Operation From Very Slow Edges
- Improved Line-Receiving Characteristics
- High Noise Immunity

**description**


Each circuit functions as an inverter, but because of the Schmitt action, it has different input threshold levels for positive-going ( $V_{T+}$ ) and negative-going ( $V_{T-}$ ) signals.

These circuits are temperature compensated and can be triggered from the slowest of input ramps and still give clean, jitter-free output signals.

**SN5414, SN54LS14 . . . J OR W PACKAGE**  
**SN7414 . . . D, N, OR NS PACKAGE**  
**SN74LS14 . . . D, DB, OR N PACKAGE**  
**(TOP VIEW)**



**SN54LS14 . . . FK PACKAGE**  
**(TOP VIEW)**



NC – No internal connection

**ORDERING INFORMATION**

| $T_A$          | PACKAGE†  |               | ORDERABLE PART NUMBER | TOP-SIDE MARKING |
|----------------|-----------|---------------|-----------------------|------------------|
| 0°C to 70°C    | PDIP – N  | Tube          | SN7414N               | SN7414N          |
|                |           | Tube          | SN74LS14N             | SN74LS14N        |
|                | SOIC – D  | Tube          | SN7414D               | 7414             |
|                |           | Tape and reel | SN7414DR              |                  |
|                |           | Tube          | SN74LS14D             | LS14             |
|                |           | Tape and reel | SN74LS14DR            |                  |
|                | SOP – NS  | Tape and reel | SN7414NSR             | SN7414           |
|                | SSOP – DB | Tape and reel | SN74LS14DBR           | LS14             |
| –55°C to 125°C | CDIP – J  | Tube          | SN5414J               | SN5414J          |
|                |           | Tube          | SNJ5414J              | SNJ5414J         |
|                |           | Tube          | SN54LS14J             | SN54LS14J        |
|                |           | Tube          | SNJ54LS14J            | SNJ54LS14J       |
|                | CFP – W   | Tube          | SNJ5414W              | SNJ5414W         |
|                |           | Tube          | SNJ54LS14W            | SNJ54LS14W       |
|                | LCCC – FK | Tube          | SNJ54LS14FK           | SNJ54LS14FK      |

† Package drawings, standard packing quantities, thermal data, symbolization, and PCB design guidelines are available at [www.ti.com/sc/package](http://www.ti.com/sc/package).



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

PRODUCTION DATA information is current as of publication date. Products conform to specifications per the terms of Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.



POST OFFICE BOX 655303 • DALLAS, TEXAS 75265


Copyright © 2002, Texas Instruments Incorporated  
On products compliant to MIL-PRF-38535, all parameters are tested unless otherwise noted. On all other products, production processing does not necessarily include testing of all parameters.

# SN5414, SN54LS14, SN7414, SN74LS14 HEX SCHMITT-TRIGGER INVERTERS

SDLS049B – DECEMBER 1983 – REVISED FEBRUARY 2002



---

## logic diagram (positive logic)



Pin numbers shown are for the D, DB, J, N, NS, and W packages.

schematic



Resistor values shown are nominal.

**SN5414, SN54LS14,  
SN7414, SN74LS14  
HEX SCHMITT-TRIGGER INVERTERS**

SDLS049B – DECEMBER 1983 – REVISED FEBRUARY 2002

**absolute maximum ratings over operating free-air temperature (unless otherwise noted)†**

|  |                |
|--|----------------|
| Supply voltage, $V_{CC}$ (see Note 1) .....                            | 7 V            |
| Input voltage: '14 .....   | 5.5 V          |
| 'LS14 .....  | 7 V            |
| Package thermal impedance, $\theta_{JA}$ (see Note 2): D package ..... | 86°C/W         |
| DB package .....   | 96°C/W         |
| N package .....  | 80°C/W         |
| NS package .....   | 76°C/W         |
| Storage temperature range, $T_{stg}$ .....                             | -65°C to 150°C |

† Stresses beyond those listed under “absolute maximum ratings” may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under “recommended operating conditions” is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

- NOTES: 1. Voltage values are with respect to network ground terminal.  
2. The package thermal impedance is calculated in accordance with JESD 51-7

**recommended operating conditions**

|                                      | SN5414 |     |      | SN7414 |     |      | UNIT |
|--------------------------------------|--------|-----|------|--------|-----|------|------|
|                                      | MIN    | NOM | MAX  | MIN    | NOM | MAX  |      |
| $V_{CC}$ Supply voltage              | 4.5    | 5   | 5.5  | 4.75   | 5   | 5.25 | V    |
| $I_{OH}$ High-level output current   |        |     | -0.8 |        |     | -0.8 | mA   |
| $I_{OL}$ Low-level output current    |        |     | 16   |        |     | 16   | mA   |
| $T_A$ Operating free-air temperature | -55    |     | 125  | 0      |     | 70   | °C   |

**electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)**

| PARAMETER                           | TEST CONDITIONS‡   | SN5414<br>SN7414 |       |      | UNIT |
|-------------------------------------|--|------------------|-------|------|------|
|                                     |  | MIN              | TYP§  | MAX  |      |
| $V_{T+}$                            | $V_{CC} = 5 V$   | 1.5              | 1.7   | 2    | V    |
| $V_{T-}$                            | $V_{CC} = 5 V$   | 0.6              | 0.9   | 1.1  | V    |
| Hysteresis<br>( $V_{T+} - V_{T-}$ ) | $V_{CC} = 5 V$   | 0.4              | 0.8   |      | V    |
| $V_{IK}$                            | $V_{CC} = \text{MIN}, I_I = -12 \text{ mA}$                  |                  |       | -1.5 | V    |
| $V_{OH}$                            | $V_{CC} = \text{MIN}, V_I = 0.6 V, I_{OH} = -0.8 \text{ mA}$ | 2.4              | 3.4   |      | V    |
| $V_{OL}$                            | $V_{CC} = \text{MIN}, V_I = 2 V, I_{OL} = 16 \text{ mA}$     |                  | 0.2   | 0.4  | V    |
| $I_{T+}$                            | $V_{CC} = 5 V, V_I = V_{T+}$                                 |                  | -0.43 |      | mA   |
| $I_{T-}$                            | $V_{CC} = 5 V, V_I = V_{T-}$                                 |                  | -0.56 |      | mA   |
| $I_I$                               | $V_{CC} = \text{MAX}, V_I = 5.5 V$                           |                  |       | 1    | mA   |
| $I_{IH}$                            | $V_{CC} = \text{MAX}, V_{IH} = 2.4 V$                        |                  |       | 40   | µA   |
| $I_{IL}$                            | $V_{CC} = \text{MAX}, V_{IL} = 0.4 V$                        |                  | -0.8  | -1.2 | mA   |
| $I_{OS}¶$                           | $V_{CC} = \text{MAX}$  | -18              |       | -55  | mA   |
| $I_{CCH}$                           | $V_{CC} = \text{MAX}$  |                  | 22    | 36   | mA   |
| $I_{CCL}$                           | $V_{CC} = \text{MAX}$  |                  | 39    | 60   | mA   |

‡ For conditions shown as MIN or MAX, use the appropriate value specified under recommended operating conditions.

§ All typical values are at  $V_{CC} = 5 V, T_A = 25^\circ C$ .

¶ Not more than one output should be shorted at a time.



**switching characteristics,  $V_{CC} = 5\text{ V}$ ,  $T_A = 25^\circ\text{C}$  (see Figure 1)**

| PARAMETER | FROM<br>(INPUT) | TO<br>(OUTPUT) | TEST CONDITIONS                             | SN5414<br>SN7414 |     |     | UNIT |
|-----------|-----------------|----------------|---|------------------|-----|-----|------|
|           |                 |                |   | MIN              | TYP | MAX |      |
| $t_{PLH}$ | A               | Y              | $R_L = 400\ \Omega$ , $C_L = 15\ \text{pF}$ |                  | 15  | 22  | ns   |
| $t_{PHL}$ |                 |                |   |                  | 15  | 22  |      |

**recommended operating conditions**

|                                      | SN54LS14 |     |      | SN74LS14 |     |      | UNIT             |
|--------------------------------------|----------|-----|------|----------|-----|------|------------------|
|                                      | MIN      | NOM | MAX  | MIN      | NOM | MAX  |                  |
| $V_{CC}$ Supply voltage              | 4.5      | 5   | 5.5  | 4.75     | 5   | 5.25 | V                |
| $I_{OH}$ High-level output current   |          |     | -0.4 |          |     | -0.4 | mA               |
| $I_{OL}$ Low-level output current    |          |     | 4    |          |     | 8    | mA               |
| $T_A$ Operating free-air temperature | -55      |     | 125  | 0        |     | 70   | $^\circ\text{C}$ |

**electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)**

| PARAMETER                           | TEST CONDITIONS†   | SN54LS14               |       |      | SN74LS14 |                        |      | UNIT          |
|-------------------------------------|--|------------------------|-------|------|----------|------------------------|------|---------------|
|                                     |  | MIN                    | TYP‡  | MAX  | MIN      | TYP‡                   | MAX  |               |
| $V_{T+}$                            | $V_{CC} = 5\text{ V}$  | 1.4                    | 1.6   | 1.9  | 1.4      | 1.6                    | 1.9  | V             |
| $V_{T-}$                            | $V_{CC} = 5\text{ V}$  | 0.5                    | 0.8   | 1    | 0.5      | 0.8                    | 1    | V             |
| Hysteresis<br>( $V_{T+} - V_{T-}$ ) | $V_{CC} = 5\text{ V}$  | 0.4                    | 0.8   |      | 0.4      | 0.8                    |      | V             |
| $V_{IK}$                            | $V_{CC} = \text{MIN}$ , $I_I = -18\text{ mA}$                            |                        |       | -1.5 |          |                        | -1.5 | V             |
| $V_{OH}$                            | $V_{CC} = \text{MIN}$ , $V_I = 0.5\text{ V}$ , $I_{OH} = -0.4\text{ mA}$ | 2.5                    | 3.4   |      | 2.7      | 3.4                    |      | V             |
| $V_{OL}$                            | $V_{CC} = \text{MIN}$ , $V_I = -1.9\text{ V}$                            | $I_{OL} = 4\text{ mA}$ |       | 0.25 | 0.4      | $I_{OL} = 4\text{ mA}$ |      | V             |
|                                     |  | $I_{OL} = 8\text{ mA}$ |       |      |          | $I_{OL} = 8\text{ mA}$ |      |               |
| $I_{T+}$                            | $V_{CC} = 5\text{ V}$ , $V_I = V_{T+}$                                   |                        | -0.14 |      |          | -0.14                  |      | mA            |
| $I_{T-}$                            | $V_{CC} = 5\text{ V}$ , $V_I = V_{T-}$                                   |                        | -0.18 |      |          | -0.18                  |      | mA            |
| $I_I$                               | $V_{CC} = \text{MAX}$ , $V_I = 7\text{ V}$                               |                        |       | 0.1  |          |                        | 0.1  | mA            |
| $I_{IH}$                            | $V_{CC} = \text{MAX}$ , $V_{IH} = 2.7\text{ V}$                          |                        |       | 20   |          |                        | 20   | $\mu\text{A}$ |
| $I_{IL}$                            | $V_{CC} = \text{MAX}$ , $V_{IL} = 0.4\text{ V}$                          |                        |       | -0.4 |          |                        | -0.4 | mA            |
| $I_{OS}^{\S}$                       | $V_{CC} = \text{MAX}$  | -20                    |       | -100 | -20      |                        | -100 | mA            |
| $I_{CCH}$                           | $V_{CC} = \text{MAX}$  |                        | 8.6   | 16   |          | 8.6                    | 16   | mA            |
| $I_{CCL}$                           | $V_{CC} = \text{MAX}$  |                        | 12    | 21   |          | 12                     | 21   | mA            |

† For conditions shown as MIN or MAX, use the appropriate value specified under recommended operating conditions.

‡ All typical values are at  $V_{CC} = 5\text{ V}$ ,  $T_A = 25^\circ\text{C}$ .

§ Not more than one output should be shorted at a time, and duration of the short-circuit should not exceed one second.


**switching characteristics,  $V_{CC} = 5\text{ V}$ ,  $T_A = 25^\circ\text{C}$  (see Figure 2)**

| PARAMETER | FROM<br>(INPUT) | TO<br>(OUTPUT) | TEST CONDITIONS                                   | MIN | TYP | MAX | UNIT |
|-----------|-----------------|----------------|---|-----|-----|-----|------|
| $t_{PLH}$ | A               | Y              | $R_L = 2\ \text{k}\Omega$ , $C_L = 15\ \text{pF}$ |     | 15  | 22  | ns   |
| $t_{PHL}$ |                 |                |   |     | 15  | 22  |      |

# SN5414, SN54LS14, SN7414, SN74LS14 HEX SCHMITT-TRIGGER INVERTERS

SDLS049B – DECEMBER 1983 – REVISED FEBRUARY 2002


## PARAMETER MEASUREMENT INFORMATION SERIES 54/74 DEVICES



- NOTES: A.  $C_L$  includes probe and jig capacitance.  
 B. All diodes are 1N3064 or equivalent.  
 C. Waveform 1 is for an output with internal conditions such that the output is low except when disabled by the output control. Waveform 2 is for an output with internal conditions such that the output is high except when disabled by the output control.  
 D. S1 and S2 are closed for  $t_{PLH}$ ,  $t_{PHL}$ ,  $t_{PHZ}$ , and  $t_{PLZ}$ ; S1 is open and S2 is closed for  $t_{PZH}$ ; S1 is closed and S2 is open for  $t_{PZL}$ .  
 E. All input pulses are supplied by generators having the following characteristics:  $PRR \leq 1$  MHz,  $Z_O \approx 50 \Omega$ ;  $t_r$  and  $t_f \leq 7$  ns for Series 54/74 devices and  $t_r$  and  $t_f \leq 2.5$  ns for Series 54S/74S devices.  
 F. The outputs are measured one at a time with one input transition per measurement.

Figure 1. Load Circuits and Voltage Waveforms

**PARAMETER MEASUREMENT INFORMATION**  
**SERIES 54LS/74LS DEVICES**



- NOTES: A.  $C_L$  includes probe and jig capacitance.  
 B. All diodes are 1N3064 or equivalent.  
 C. Waveform 1 is for an output with internal conditions such that the output is low except when disabled by the output control. Waveform 2 is for an output with internal conditions such that the output is high except when disabled by the output control.  
 D. S1 and S2 are closed for  $t_{PLH}$ ,  $t_{PHL}$ ,  $t_{PHZ}$ , and  $t_{PLZ}$ ; S1 is open and S2 is closed for  $t_{PZH}$ ; S1 is closed and S2 is open for  $t_{PZL}$ .  
 E. Phase relationships between inputs and outputs have been chosen arbitrarily for these examples.  
 F. All input pulses are supplied by generators having the following characteristics:  $PRR \leq 1$  MHz,  $Z_O \approx 50 \Omega$ ,  $t_r \leq 1.5$  ns,  $t_f \leq 2.6$  ns.  
 G. The outputs are measured one at a time with one input transition per measurement.

**Figure 2. Load Circuits and Voltage Waveforms**

TYPICAL CHARACTERISTICS OF '14 CIRCUITS†

POSITIVE-GOING THRESHOLD VOLTAGE  
 vs  
 FREE-AIR TEMPERATURE




Figure 3

NEGATIVE-GOING THRESHOLD VOLTAGE  
 vs  
 FREE-AIR TEMPERATURE




Figure 4

HYSTERESIS  
 vs  
 FREE-AIR TEMPERATURE




Figure 5

† Data for temperatures below 0°C and above 70°C and supply voltage below 4.75 V and above 5.25 V are applicable for SN5414 only.

**TYPICAL CHARACTERISTICS OF '14 CIRCUIT†**




Figure 6




Figure 7




Figure 8




Figure 9


† Data for temperatures below  $0^\circ\text{C}$  and above  $70^\circ\text{C}$  and supply voltage below 4.75 V and above 5.25 V are applicable for SN5414 only.

**SN5414, SN54LS14,  
SN7414, SN74LS14  
HEX SCHMITT-TRIGGER INVERTERS**

SDLS049B – DECEMBER 1983 – REVISED FEBRUARY 2002


**TYPICAL CHARACTERISTICS OF 'LS14 CIRCUITS†**

**POSITIVE-GOING THRESHOLD VOLTAGE  
vs  
FREE-AIR TEMPERATURE**




**Figure 10**

**NEGATIVE-GOING THRESHOLD VOLTAGE  
vs  
FREE-AIR TEMPERATURE**




**Figure 11**

**HYSTERESIS  
vs  
FREE-AIR TEMPERATURE**



**Figure 12**

**DISTRIBUTION OF UNITS  
FOR HYSTERESIS**



**Figure 13**

† Data for temperatures below 0°C and above 70°C and supply voltage below 4.75 V and above 5.25 V are applicable for SN5414 only.

**TYPICAL CHARACTERISTICS OF 'LS14 CIRCUITS†**




Figure 14





Figure 15

† Data for temperatures below  $0^\circ\text{C}$  and above  $70^\circ\text{C}$  and supply voltage below 4.75 V and above 5.25 V are applicable for SN5414 only.


**SN5414, SN54LS14,  
SN7414, SN74LS14  
HEX SCHMITT-TRIGGER INVERTERS**

SDLS049B – DECEMBER 1983 – REVISED FEBRUARY 2002


**TYPICAL APPLICATION DATA**




**TTL System Interface  
for Slow Input Waveforms**




**Pulse Shaper**




**Multivibrator**



**Threshold Detector**



**Pulse Stretcher**



## IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Mailing Address:

Texas Instruments  
Post Office Box 655303  
Dallas, Texas 75265